

View Online at <https://aerobasegroup.com/nsn/5915-00-502-4465>

Overall Length:

1.580 inches

Body Length:

1.400 inches

Body Width:

0.450 inches

Body Height:

0.450 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.050 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.650 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Reference Frequency Per Function:

109.35 megahertz blank

Source Impedance Rating Per Function:

200.0 ohms blank

Load Impedance Per Function:

200.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 solder stud input 1st function

Specified Frequencies Of Discrimination Per Function:

5.00 megahertz blank and 109.347 megahertz blank and 109.353 megahertz blank and 200.00 megahertz blank

Thread Size:

0.086 inches

Body Material:

Metal

Frequency Band Width Per Function:

109.347 megahertz blank and 109.353 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 60.0 blank

Special Features:

Mtg holes on width, mtg studs on length

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0