

View Online at https://aerobasegroup.com/nsn/5915-00-503-1920

1.868 inchesBody Length:1.798 inchesBody Width:0.750 inchesBody Height:1.718 inchesUnthreaded Mounting Hole Diameter:0.125 inchesSource Impedance Rating Per Function:50.0 ohms 2nd radio interferenceLoad Impedance Per Function:50.0 ohms 2nd radio interferenceDoperating Current Rating Per Function In Amps:5.0 2nd radio interferenceInclosure Type:EncasedMounting Facility Type And Quantity:3 unthreaded holeFunctional Terminal Type And Quantity:2 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:30.0 volts dc 2nd radio interference 2nd functionBody Material:MetalStyle Designator:Rectangular terminal/terminals on one surfaceShelf Life:N/aUnit Of Measure:-Pemilitarization:Yes - demi/mliFiig:	Overall Height:
Body Length: 1.798 inches Body Width: 0.750 inches Body Height: 1.718 inches Unthreaded Mounting Hole Diameter: 0.125 inches Unthreaded Mounting Hole Diameter: 0.125 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Operating Current Rating Per Function In Amps: 50.0 ohms 2nd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	-
1.798 inches Body Width: O.750 inches Body Height: O.750 inches Body Height: O.7151 inches Unthreaded Mounting Hole Diameter: O.125 inches Source Impedance Rating Per Function: O.0 ohms 2nd radio interference Load Impedance Per Function: O.0 ohms 2nd radio interference Operating Current Rating Per Function In Amps: O.0 ohms 2nd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: Operating Voltage Rating And Type Per Function: Onerating Voltage Rating And Type Per Function: Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Body Widh: 0.750 inches Body Height: 1.718 inches Unthreaded Mounting Hole Diameter: 0.125 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Operating Current Rating Per Function In Amps: 5.0 2nd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
0.750 inchesBody Height:1.718 inchesUnthreaded Mounting Hole Diameter:0.125 inchesSource Impedance Rating Per Function:50.0 ohms 2nd radio interferenceLoad Impedance Per Function:50.0 ohms 2nd radio interferenceDoperating Current Rating Per Function In Amps:50.0 znd radio interferenceInclosure Type:EncasedMounting Facility Type And Quantity:3 unthreaded holeFunctional Terminal Type And Quantity:2 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:30.0 volts de 2nd radio interference 2nd functionBody Material:MetalStyle Designator:Rectangular terminal/terminals on one surfaceShelf Life:N/aUnit Of Measure:Demilitarization:Yes - demil/mli	
Body Height: 1.718 inches Unthreaded Mounting Hole Diameter: 0.125 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Operating Current Rating Per Function In Amps: 5.0 2nd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
1.718 inches 1.718 inches Unthreaded Mounting Hole Diameter: 0.125 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Operating Current Rating Per Function In Amps: 5.0 2nd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Unthreaded Mounting Hole Diameter:0.125 inchesSource Impedance Rating Per Function:50.0 ohms 2nd radio interferenceLoad Impedance Per Function:50.0 ohms 2nd radio interferenceDeprating Current Rating Per Function In Amps:5.0 2nd radio interferenceInclosure Type:EncasedMounting Facility Type And Quantity:3 unthreaded holeFunctional Terminal Type And Quantity:2 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:30.0 volts dc 2nd radio interference 2nd functionBody Material:MetalStyle Designator:Rectangular terminal/terminals on one surfaceShelf Life:N/aUnit Of Measure:Demilitarization:Yes - demil/mli	
0.125 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Operating Current Rating Per Function In Amps: 5.0 2nd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Operating Current Rating Per Function In Amps: 5.0 2nd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	-
50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Operating Current Rating Per Function In Amps: 5.0 2nd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Load Impedance Per Function: 50.0 ohms 2nd radio interference Operating Current Rating Per Function In Amps: 5.0 2nd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
50.0 ohms 2nd radio interference Operating Current Rating Per Function In Amps: 5.0 2nd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Operating Current Rating Per Function In Amps: 5.0 2nd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
5.0 2nd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Inclosure Type: Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Encased Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Mounting Facility Type And Quantity: 3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
3 unthreaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Operating Voltage Rating And Type Per Function: 30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Functional Terminal Type And Quantity:
30.0 volts dc 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	2 tab, solder lug output 2nd function
Body Material: Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Operating Voltage Rating And Type Per Function:
Metal Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	30.0 volts dc 2nd radio interference 2nd function
Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Body Material:
Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Metal
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Style Designator:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Rectangular terminal/terminals on one surface
Unit Of Measure: Demilitarization: Yes - demil/mli	Shelf Life:
 Demilitarization: Yes - demil/mli	N/a
Yes - demil/mli	Unit Of Measure:
Yes - demil/mli	
	Demilitarization:
Fiig:	Yes - demil/mli
	Fiig:
A047b0	A047b0