NSN 5915-00-504-8064

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-504-8064

Overall Height:
2.656 inches
Body Length:
1.391 inches
Body Width:
1.391 inches
Body Height:
2.312 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.875 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.875 inches
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Reference Frequency Per Function:
1.0 kilohertz blank
Input Impedance Per Function W/load:
50.0 kilohms blank
Output Impedance Per Function W/source Across Input:
50.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Tiermetically Sealed
Mounting Facility Type And Quantity:
•
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 threaded stud
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity:
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function:
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 300.00 hertz blank and 3.50 kilohertz blank and 5.50 kilohertz blank and 11.00 kilohertz blank
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 300.00 hertz blank and 3.50 kilohertz blank and 5.50 kilohertz blank and 11.00 kilohertz blank Thread Size:
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 300.00 hertz blank and 3.50 kilohertz blank and 5.50 kilohertz blank and 11.00 kilohertz blank Thread Size: 0.112 inches
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 300.00 hertz blank and 3.50 kilohertz blank and 5.50 kilohertz blank and 11.00 kilohertz blank Thread Size: 0.112 inches Frequency Band Width Per Function:
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 300.00 hertz blank and 3.50 kilohertz blank and 5.50 kilohertz blank and 11.00 kilohertz blank Thread Size: 0.112 inches Frequency Band Width Per Function: 300.00 hertz blank and 3.50 kilohertz blank
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 300.00 hertz blank and 3.50 kilohertz blank and 5.50 kilohertz blank and 11.00 kilohertz blank Thread Size: 0.112 inches Frequency Band Width Per Function: 300.00 hertz blank and 3.50 kilohertz blank Discrimination At Specificationified Frequencies Per Function In Decibels:

N/a

Shelf Life:

NSN 5915-00-504-8064

Low Pass Filter - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A047b0