

View Online at https://aerobasegroup.com/nsn/5915-00-504-8870

1.906 inches Body Length: 1.156 inches Body Width: 1.031 inches Body Height: 0.703 inches Unthreaded Mounting Hole Diameter: 0.141 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.422 inches and 1.454 inches Operating Tempurature Range: -55.0+100.0 degrees celsius Source Impedance Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Mertz: 1000.0 blank Poperating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: Solo.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltag	
Body Length: 1.156 inches Body Width: 1.031 inches Body Height: 0.703 inches Unthreaded Mounting Hole Diameter: 0.141 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.422 inches and 1.454 inches Operating Tempurature Range: -55.0100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 1000.0 millivoits ac blank Principal Circuitry Type Per Function: 1nductance-capacitance blank Output Terminal Identification: 1 Inductance-capacitance blank Mounting Facility Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovoits at sea level Operating Voltage Rating And Type Per Function: 125.0 voits ac bl	Overall Length:
1.15 inches Body Width: 1.031 inches Body Height: 0.703 inches Unthreaded Mounting Hole Diameter: 0.141 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Lengthe Between 1.422 inches and 1.454 inches Operating Tempurature Range: -55.0100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Hertz: 3.0 blank Maximum Voltage Drop Per Function In Amps: 3.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inductance-capacitance blank Mounting Facility Type And Quantity: 1 untreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Ty	
Body Width: 1.031 inches Body Height: 0.703 inches Unthreaded Mounting Hole Diameter: 0.141 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.422 inches and 1.454 inches Operating Tempurature Range: -55.0/+ 100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: 10utcance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 untit autoin I Jipe And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: <td< td=""><td></td></td<>	
1.031 inches Body Height: 0.703 inches Unthreaded Mounting Hole Diameter: 0.141 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.422 inches and 1.454 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 1000.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Harmetically sealed Moutting Facility Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovotts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: 125.0 volts ac blank<	
Body Height: 0.703 inches Unthreaded Mounting Hole Diameter: 0.141 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.422 inches and 1.454 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Hermetically sealed Mounting Facility Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: 125.0 volts ac blank	-
0.703 inches Unthreaded Mounting Hole Diameter: 0.141 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.422 inches and 1.454 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: 125.0 volts ac blank	
Untreaded Mounting Hole Diameter: 0.141 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.422 inches and 1.454 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function In Amps: 3.0 blank Principal Circuitry Type Per Function: 100.0 millivolts as blank Principal Circuitry Type Per Function: 11 Inductance-capacitance blank Output Terminal Identification: 1 Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 12.5.0 volts ac blank Syle Designato:: Rectangular terminal/terminals on opposite surfaces Shelf Life:	
0.141 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.422 inches and 1.454 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 50.0 onillivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Syle Designato:: Rectangular terminal/terminals on opposite surfaces	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.422 inches and 1.454 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: 10uctance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank	-
Between 1.422 inches and 1.454 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 50.0 omillivolts ac blank Principal Circuitry Type Per Function: 10ductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	
Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts as ea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank	
 -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: 	Between 1.422 inches and 1.454 inches
Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	Operating Tempurature Range:
50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maxinum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maxinum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	-55.0/+100.0 degrees celsius
Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	Source Impedance Rating Per Function:
50.0 oms blank Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maxinum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maxinum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz: 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	Load Impedance Per Function:
 1000.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: 	50.0 ohms blank
Operating Current Rating Per Function In Amps:3.0 blankMaximum Voltage Drop Per Function:500.0 millivolts ac blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankOutput Terminal Identification:1Inclosure Type:Hermetically sealedMounting Facility Type And Quantity:2 unthreaded holeFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionMaximum Dielectric Withstanding Ac Rms Voltage:1000.0 kilovolts at sea levelOperating Voltage Rating And Type Per Function:125.0 volts ac blankStyle Designator:Rectangular terminal/terminals on opposite surfacesShelf Life:	Power Line Frequency Rating Per Function In Hertz:
3.0 blank Maximum Voltage Drop Per Function: 500.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	1000.0 blank
Maximum Voltage Drop Per Function:500.0 millivolts ac blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankOutput Terminal Identification:1Inclosure Type:Hermetically sealedMounting Facility Type And Quantity:2 unthreaded holeFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionMaximum Dielectric Withstanding Ac Rms Voltage:1000.0 kilovolts at sea levelOperating Voltage Rating And Type Per Function:125.0 volts ac blankStyle Designator:Rectangular terminal/terminals on opposite surfacesShelf Life:	Operating Current Rating Per Function In Amps:
500.0 millivolts ac blank Principal Circuitry Type Per Function: Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	3.0 blank
Principal Circuitry Type Per Function:Inductance-capacitance blankOutput Terminal Identification:1IInclosure Type:Hermetically sealedMounting Facility Type And Quantity:2 unthreaded holeFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionMaximum Dielectric Withstanding Ac Rms Voltage:1000.0 kilovolts at sea levelOperating Voltage Rating And Type Per Function:125.0 volts ac blankStyle Designator:Rectangular terminal/terminals on opposite surfacesShelf Life:	Maximum Voltage Drop Per Function:
Inductance-capacitance blank Output Terminal Identification: 1 Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	500.0 millivolts ac blank
Output Terminal Identification:1Inclosure Type:Hermetically sealedMounting Facility Type And Quantity:2 unthreaded holeFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionMaximum Dielectric Withstanding Ac Rms Voltage:1000.0 kilovolts at sea levelOperating Voltage Rating And Type Per Function:125.0 volts ac blankStyle Designator:Rectangular terminal/terminals on opposite surfacesShelf Life:	Principal Circuitry Type Per Function:
1Inclosure Type:Hermetically sealedMounting Facility Type And Quantity:2 unthreaded holeFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionMaximum Dielectric Withstanding Ac Rms Voltage:1000.0 kilovolts at sea levelOperating Voltage Rating And Type Per Function:125.0 volts ac blankStyle Designator:Rectangular terminal/terminals on opposite surfacesShelf Life:	Inductance-capacitance blank
Inclosure Type:Hermetically sealedMounting Facility Type And Quantity:2 unthreaded holeFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionMaximum Dielectric Withstanding Ac Rms Voltage:1000.0 kilovolts at sea levelOperating Voltage Rating And Type Per Function:125.0 volts ac blankStyle Designator:Rectangular terminal/terminals on opposite surfacesShelf Life:	Output Terminal Identification:
 Hermetically sealed Mounting Facility Type And Quantity: 2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: 	1
Mounting Facility Type And Quantity:2 unthreaded holeFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionMaximum Dielectric Withstanding Ac Rms Voltage:1000.0 kilovolts at sea levelOperating Voltage Rating And Type Per Function:125.0 volts ac blankStyle Designator:Rectangular terminal/terminals on opposite surfacesShelf Life:	Inclosure Type:
2 unthreaded hole Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	Hermetically sealed
 Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: 	Mounting Facility Type And Quantity:
1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	2 unthreaded hole
Maximum Dielectric Withstanding Ac Rms Voltage: 1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	Functional Terminal Type And Quantity:
1000.0 kilovolts at sea level Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	1 tab, solder lug output 2nd function
Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	Maximum Dielectric Withstanding Ac Rms Voltage:
125.0 volts ac blank Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	1000.0 kilovolts at sea level
Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:	Operating Voltage Rating And Type Per Function:
Rectangular terminal/terminals on opposite surfaces Shelf Life:	125.0 volts ac blank
Shelf Life:	Style Designator:
	Rectangular terminal/terminals on opposite surfaces
N1/-	Shelf Life:
N/a	N/a



Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A047b0