

View Online at <https://aerobasegroup.com/nsn/5915-00-506-7515>

Overall Height:

1.246 inches

Body Length:

2.250 inches

Body Width:

1.125 inches

Body Height:

0.968 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.600 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

+55.0/+85.0 degrees celsius

Reference Frequency Per Function:

3.1 megahertz blank

Source Impedance Rating Per Function:

4.0 kilohms blank

Load Impedance Per Function:

150.0 ohms blank

Input Impedance Per Function W/load:

4.0 kilohms blank

Output Impedance Per Function W/source Across Input:

150.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

2.95 megahertz blank and 3.065 megahertz blank and 3.135 megahertz blank and 3.25 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

3.065 megahertz blank and 3.135 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 4.4 blank and 4.4 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0