

View Online at <https://aerobasegroup.com/nsn/5915-00-509-4291>

Overall Height:

0.758 inches

Body Length:

2.730 inches

Body Width:

0.500 inches

Body Height:

0.578 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.500 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Reference Frequency Per Function:

450.0 kilohertz blank

Source Impedance Rating Per Function:

20.0 ohms blank

Load Impedance Per Function:

20.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

8.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

420.00 kilohertz blank and 447.00 kilohertz blank and 453.00 kilohertz blank and 500.00 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

447.00 kilohertz blank and 453.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 3.5 blank and 3.5 blank and 40.0 blank

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

13499-580-7037-001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0