

View Online at https://aerobasegroup.com/nsn/5915-00-519-4280

Overall Length:
1.781 inches
Body Length:
1.250 inches
Body Outside Diameter:
0.670 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
1000.0 blank
Operating Current Rating Per Function In Amps:
0.05 blank and 0.05 blank
Maximum Voltage Drop Per Function:
0.4 volts dc blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Maximum Tempurature Rise:
25.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
Features Provided:
Nut and washer
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Maximum Dielectric Withstanding Ac Rms Voltage:
230.0 volts at sea level and 143.7 volts at altitude
Operating Voltage Rating And Type Per Function:
115.0 volts ac blank and 500.0 volts dc blank
Thread Size:
0.250 inches
Body Material:
Metal



Maximum Dielectric Withstanding Dc Voltage:

1.0 kilovolts at sea level and 625.0 volts at altitude

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0