

View Online at <https://aerobasegroup.com/nsn/5915-00-523-1878>

Overall Height:

Between 3.088 inches and 3.110 inches

Body Length:

Between 3.875 inches and 3.937 inches

Body Width:

Between 1.407 inches and 1.469 inches

Body Height:

Between 2.532 inches and 2.646 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.672 inches and 2.704 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-65.0/+185.0 degrees fahrenheit

Reference Frequency Per Function:

56.0 kilohertz blank

Input Impedance Per Function W/load:

135.0 ohms blank

Output Impedance Per Function W/source Across Input:

40.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

9.2 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

50.00 kilohertz blank and 52.00 kilohertz blank and 60.00 kilohertz blank and 62.00 kilohertz blank

Thread Size:

0.190 inches

Frequency Band Width Per Function:

52.00 kilohertz blank and 60.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

75.0 blank and 55.0 blank and 55.0 blank and 75.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0