

View Online at <https://aerobasegroup.com/nsn/5915-00-523-1878>

**Overall Height:**

Between 3.088 inches and 3.110 inches

**Body Length:**

Between 3.875 inches and 3.937 inches

**Body Width:**

Between 1.407 inches and 1.469 inches

**Body Height:**

Between 2.532 inches and 2.646 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.672 inches and 2.704 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Operating Temperature Range:**

-65.0/+185.0 degrees fahrenheit

**Reference Frequency Per Function:**

56.0 kilohertz blank

**Input Impedance Per Function W/load:**

135.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

40.0 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance-resistance blank

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

9.2 blank

**Functional Terminal Type And Quantity:**

2 tab, solder lug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

50.00 kilohertz blank and 52.00 kilohertz blank and 60.00 kilohertz blank and 62.00 kilohertz blank

**Thread Size:**

0.190 inches

**Frequency Band Width Per Function:**

52.00 kilohertz blank and 60.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

75.0 blank and 55.0 blank and 55.0 blank and 75.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0