## NSN 5915-00-567-9523

Radio Frequency Interference Filter - Page 1 of 1



-567-9523

| View Online at https://aerobasegroup.com/nsn/5915-00- |
|---|
| Operating Tempurature Range:                          |
| -54.0/+55.0 degrees celsius                           |
| Power Line Frequency Rating Per Function In Hertz:    |
| 400.0 3rd radio interference                          |
| Operating Current Rating Per Function In Amps:        |
| 5.23 2nd radio interference                           |
| Maximum Voltage Drop Per Function:                    |
| 280.0 millivolts dc 4th radio interference            |
| Principal Circuitry Type Per Function:                |
| Inductance-capacitance 3rd radio interference         |
| Input Terminal Manufacturer Code:                     |
| 96906   |
| Input Terminal Identification:                        |
| Ms27335t18a11p  |
| Inclosure Type:                                       |
| Hermetically sealed                                   |
| Functional Terminal Type And Quantity:                |
| 3 tab, solder lug output 2nd function                 |
| Operating Voltage Rating And Type Per Function:       |
| 115.0 volts ac 3rd radio interference 3rd function    |
| Body Material:  |
| Metal   |
| Maximum Dielectric Withstanding Dc Voltage:           |
| 400.0 volts at sea level                              |
| <b>Body Surface Treatment:</b>                        |
| Tin   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                      |
|   |
| Demilitarization:                                     |

No Fiig: A047b0