

View Online at https://aerobasegroup.com/nsn/5915-00-570-4455

Overall Length: 3.748 inches Body Length: 2.687 inches Body Outside Diameter: 0.750 inches Vibration Resistance Range In Hertz: +5.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius
Body Length: 2.687 inches Body Outside Diameter: 0.750 inches Vibration Resistance Range In Hertz: +5.0/+2000.0 Operating Tempurature Range:
2.687 inches Body Outside Diameter: 0.750 inches Vibration Resistance Range In Hertz: +5.0/+2000.0 Operating Tempurature Range:
Body Outside Diameter: 0.750 inches Vibration Resistance Range In Hertz: +5.0/+2000.0 Operating Tempurature Range:
0.750 inches Vibration Resistance Range In Hertz: +5.0/+2000.0 Operating Tempurature Range:
Vibration Resistance Range In Hertz: +5.0/+2000.0 Operating Tempurature Range:
+5.0/+2000.0 Operating Tempurature Range:
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Average Life Rating In Hours:
2000.0
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Operating Current Rating Per Function In Amps:
0.1 blank
Maximum Voltage Drop Per Function:
300.0 millivolts dc blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
Functional Terminal Type And Quantity:
1 tab, solder lug input and 1 tab, solder lug output
Operating Voltage Rating And Type Per Function:
100.0 volts dc blank
Thread Size:
0.437 inches
Style Designator:
Round terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

## NSN 5915-00-570-4455

Radio Frequency Interference Filter - Page 2 of 2

**Fiig:** A047b0

