

View Online at <https://aerobasegroup.com/nsn/5915-00-577-9015>

Overall Height:

Between 3.063 inches and 3.187 inches

Body Length:

2.125 inches

Body Width:

1.938 inches

Body Height:

2.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.546 inches and 1.578 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.859 inches and 0.891 inches

Operating Temperature Range:

-0.0/+65.0 degrees celsius

Reference Frequency Per Function:

300.0 kilohertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance-resistance blank

Output Terminal Manufacturer Code:

92860

Output Terminal Identification:

45975

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug input 1st function

Specified Frequencies Of Discrimination Per Function:

99.00 kilohertz blank and 249.00 kilohertz blank and 306.00 kilohertz blank and 1.70 megahertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

294.00 kilohertz blank and 306.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 3.0 blank and 3.0 blank and 70.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0