NSN 5915-00-583-1964

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-583-1964

Overall Length: 4.093 inches **Body Length:** Between 3.469 inches and 3.531 inches **Body Outside Diameter:** Between 0.760 inches and 0.790 inches Vibration Resistance Range In Hertz: +5.0/+500.0 **Operating Tempurature Range:** -40.0/+85.0 degrees celsius **Reference Frequency Per Function:** 300.0 kilohertz blank **Load Impedance Per Function:** 50.0 kilohms blank Input Impedance Per Function W/load: 35.0 kilohms blank **Output Impedance Per Function W/source Across Input:** 35.0 kilohms blank **Inclosure Type:** Hermetically sealed Insertion Loss At Reference Frequency Per Function In Decibels: 15.0 blank **Functional Terminal Type And Quantity:** 2 wire hook output 2nd function **Maximum Dielectric Withstanding Ac Rms Voltage:** 500.0 volts at altitude **Specified Frequencies Of Discrimination Per Function:** 295.80 kilohertz blank and 297.00 kilohertz blank and 299.65 kilohertz blank and 301.00 kilohertz blank **Frequency Band Width Per Function:** 297.00 kilohertz blank and 299.00 kilohertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 60.0 blank and 2.5 blank and 2.5 blank and 60.0 blank Style Designator: Round terminal/terminals on opposite surfaces **Test Data Document:** 13499-526-9311-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5915-00-583-1964

Band Pass Filter - Page 2 of 2



Fiig:

A047b0