

View Online at <https://aerobasegroup.com/nsn/5915-00-583-1966>

Overall Length:

2.344 inches

Body Outside Diameter:

0.438 inches

Vibration Resistance Range In Hertz:

+5.0/+500.0

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Reference Frequency Per Function:

455.0 kilohertz blank

Source Impedance Rating Per Function:

100.0 kilohms blank

Load Impedance Per Function:

100.0 kilohms blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 clamp

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 kilovolts at sea level

Specified Frequencies Of Discrimination Per Function:

385.00 kilohertz blank and 437.00 kilohertz blank and 473.00 kilohertz blank and 555.00 kilohertz blank

Frequency Band Width Per Function:

437.00 kilohertz blank and 473.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

70.0 blank and 3.5 blank and 3.5 blank and 70.0 blank

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0