

View Online at <https://aerobasegroup.com/nsn/5915-00-589-2980>

**Body Length:**

Between 1.187 inches and 1.219 inches

**Body Width:**

Between 0.702 inches and 0.734 inches

**Body Height:**

Between 1.452 inches and 1.484 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 0.568 inches and 0.578 inches

**Operating Temperature Range:**

-30.0/+55.0 degrees celsius

**Reference Frequency Per Function:**

700.0 kilohertz blank

**Source Impedance Rating Per Function:**

1000.0 kilohms blank

**Load Impedance Per Function:**

1000.0 kilohms blank

**Input Impedance Per Function W/load:**

1000.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

1000.0 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

0.00 hertz blank and 1.20 megahertz blank and 2.00 megahertz blank and 2.10 megahertz blank

**Thread Size:**

0.138 inches

**Frequency Band Width Per Function:**

0.00 hertz blank and 1.20 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

1.0 blank and 1.0 blank and 25.0 blank and 25.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0