

View Online at <https://aerobasegroup.com/nsn/5915-00-589-2980>

Body Length:

Between 1.187 inches and 1.219 inches

Body Width:

Between 0.702 inches and 0.734 inches

Body Height:

Between 1.452 inches and 1.484 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.568 inches and 0.578 inches

Operating Temperature Range:

-30.0/+55.0 degrees celsius

Reference Frequency Per Function:

700.0 kilohertz blank

Source Impedance Rating Per Function:

1000.0 kilohms blank

Load Impedance Per Function:

1000.0 kilohms blank

Input Impedance Per Function W/load:

1000.0 kilohms blank

Output Impedance Per Function W/source Across Input:

1000.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

0.00 hertz blank and 1.20 megahertz blank and 2.00 megahertz blank and 2.10 megahertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

0.00 hertz blank and 1.20 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 25.0 blank and 25.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0