NSN 5915-00-593-3676

High Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-593-3676

Overall Length: 3.124 inches **Body Length:** Between 1.995 inches and 2.005 inches **Body Width:** Between 0.995 inches and 1.005 inches **Body Height:** Between 1.995 inches and 2.005 inches **Unthreaded Mounting Hole Diameter:** Between 0.183 inches and 0.193 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** Between 2.370 inches and 2.380 inches **Vibration Resistance Range In Hertz:** +10.0/+55.0 **Operating Tempurature Range:** -55.0/+70.0 degrees celsius **Reference Frequency Per Function:** 3.01 megahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 400.00 hertz blank and 20.00 kilohertz blank and 6.00 megahertz blank

Frequency Band Width Per Function:

20.00 kilohertz blank and 6.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

50.0 blank and 50.0 blank and 3.0 blank and 3.0 blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

NSN 5915-00-593-3676

High Pass Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0