## NSN 5915-00-610-6099

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-610-6099

Overall Length:
3.122 inches
Body Length:
2.000 inches
Body Width:
3.000 inches
Body Height:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.200 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.687 inches
Reference Frequency Per Function:
312.5 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Input Terminal Manufacturer Code:
80058
Input Terminal Identification:
Ug-535/u
Output Terminal Manufacturer Code:
80058
Output Terminal Identification:
Ug-535/u
Voltage Standing Wave Ratio Per Function:
1.4 blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
3 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.3 blank
Functional Terminal Type And Quantity:
1 connector, receptacle output 2nd function
Specified Frequencies Of Discrimination Per Function:
225.00 megahertz blank and 400.00 megahertz blank and 950.00 megahertz blank and 1.25 gigahertz blank
Thread Size:

0.164 inches

# NSN 5915-00-610-6099

Low Pass Filter - Page 2 of 2



#### Body Material:

Metal

Frequency Band Width Per Function:

225.00 megahertz blank and 400.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 60.0 blank and 60.0 blank

### **Precious Material And Location:**

Body gold and body silver

**Precious Material:** 

Gold and silver

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A047b0