

View Online at <https://aerobasegroup.com/nsn/5915-00-615-0565>

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Reference Frequency Per Function:

300.0 kilohertz blank

Source Impedance Rating Per Function:

50.0 kilohms blank

Load Impedance Per Function:

50.0 kilohms blank

Input Impedance Per Function W/load:

35.0 kilohms blank

Output Impedance Per Function W/source Across Input:

35.0 kilohms blank

Principal Circuitry Type Per Function:

Electromechanical blank

Inclosure Type:

Hermetically sealed

Insertion Loss At Reference Frequency Per Function In Decibels:

2.5 blank

Functional Terminal Type And Quantity:

2 wire hook output 2nd function

Specified Frequencies Of Discrimination Per Function:

294.60 kilohertz blank and 296.50 kilohertz blank and 303.00 kilohertz blank and 305.40 kilohertz blank

Frequency Band Width Per Function:

296.50 kilohertz blank and 303.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 2.5 blank and 2.5 blank and 60.0 blank

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0