

View Online at <https://aerobasegroup.com/nsn/5915-00-628-5186>

Overall Height:

2.625 inches

Body Length:

1.562 inches

Body Width:

1.375 inches

Body Height:

2.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.000 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.875 inches

Operating Temperature Range:

-40.0/+160.0 degrees fahrenheit

Reference Frequency Per Function:

1.6 kilohertz blank

Input Impedance Per Function W/load:

20.0 kilohms blank

Output Impedance Per Function W/source Across Input:

20.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

800.00 hertz blank and 1.57 kilohertz blank and 1.63 kilohertz blank and 3.20 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.57 kilohertz blank and 1.63 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 3.0 blank and 3.0 blank and 40.0 blank

Special Features:

Use 3 pounds force in terminal strength test

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0