NSN 5915-00-632-2375

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-632-2375

Overall Length:
7.500 inches
Overall Height:
1.250 inches
Body Length:
6.000 inches
Body Width:
3.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
5.625 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.625 inches
Operating Tempurature Range:
+0.0/+50.0 degrees celsius
Reference Frequency Per Function:
17.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
1.5 blank
Average Power Rating Per Function:
100.0 watts blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.5 blank
Functional Terminal Type And Quantity:
1 connector, receptacle output 2nd function
Specified Frequencies Of Discrimination Per Function:
2.00 megahertz blank and 32.00 megahertz blank and 80.00 megahertz blank and 1.00 gigahertz blank
Thread Size:
0.112 inches
Frequency Band Width Per Function:

2.00 megahertz blank and 32.00 megahertz blank

NSN 5915-00-632-2375

Low Pass Filter - Page 2 of 2



Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 100.0 blank and 100.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

2.0 megahertz blank and 32.0 megahertz blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0