## NSN 5915-00-632-7821

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-632-7821

| Overall Height:  |
|--|
| 2.125 inches   |
| Body Length:   |
| 3.000 inches   |
| Body Width:  |
| 1.250 inches   |
| Body Height:   |
| 0.875 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.500 inches   |
| Vibration Resistance Range In Hertz:   |
| +10.0/+55.0  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:  |
| 0.750 inches   |
| Operating Tempurature Range:   |
| -55.0/+105.0 degrees celsius   |
| Average Life Rating In Hours:  |
| 250.0  |
| Source Impedance Rating Per Function:  |
| 50.0 ohms 4th radio interference   |
| Load Impedance Per Function:   |
| 50.0 ohms 4th radio interference   |
| Power Line Frequency Rating Per Function In Hertz:                           |
| 400.0 4th radio interference   |
| Operating Current Rating Per Function In Amps:                               |
| 30.0 1st radio interference  |
| Mounting Facility Screw Thread Series Designator:                            |
| Unf  |
| Inclosure Type:  |
| Encased  |
| Mounting Facility Type And Quantity:   |
| 2 threaded hole  |
| Functional Terminal Type And Quantity:                                       |
| 4 threaded stud output 2nd function  |
| Maximum Dielectric Withstanding Ac Rms Voltage:                              |
| 416.0 volts at sea level   |

Thread Size:

0.190 inches

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Operating Voltage Rating And Type Per Function: 208.0 volts ac 4th radio interference 4th function

## NSN 5915-00-632-7821

Radio Frequency Interference Filter - Page 2 of 2



N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0