

View Online at https://aerobasegroup.com/nsn/5915-00-632-8643

| Overall Length: |
|--|
| 4.500 inches |
| Body Length: |
| 3.500 inches |
| Body Width: |
| 1.125 inches |
| Body Height: |
| 1.125 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+55.0 |
| Operating Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| Average Life Rating In Hours: |
| 250.0 |
| Source Impedance Rating Per Function: |
| 50.0 ohms blank |
| Load Impedance Per Function: |
| 50.0 ohms blank |
| Operating Current Rating Per Function In Amps: |
| 0.075 blank |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 1 threaded hole |
| Functional Terminal Type And Quantity: |
| 1 tab, solder lug output 2nd function |
| Operating Voltage Rating And Type Per Function: |
| 150.0 volts dc blank |
| Thread Size: |
| 0.138 inches |
| Body Material: |
| Metal |
| Maximum Dielectric Withstanding Dc Voltage: |
| 300.0 volts at sea level |
| Body Surface Treatment: |
| Tin |
| Style Designator: |
| Destancy des terminal/terminals an ennesite curfesse |

Rectangular terminal/terminals on opposite surfaces

Radio Frequency Interference Filter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0