

View Online at <https://aerobasegroup.com/nsn/5915-00-643-8302>

Overall Height:

4.938 inches

Body Length:

Between 1.484 inches and 1.516 inches

Body Width:

Between 1.484 inches and 1.516 inches

Body Height:

Between 4.484 inches and 4.516 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.953 inches and 0.985 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.953 inches and 0.985 inches

Reference Frequency Per Function:

1.35 kilohertz blank

Input Impedance Per Function W/load:

50.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 solder stud input 1st function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.00 kilohertz blank and 3.10 kilohertz blank and 3.14 kilohertz blank and 6.28 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 kilohertz blank and 3.10 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 40.00 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0