

View Online at <https://aerobasegroup.com/nsn/5915-00-643-8302>

**Overall Height:**

4.938 inches

**Body Length:**

Between 1.484 inches and 1.516 inches

**Body Width:**

Between 1.484 inches and 1.516 inches

**Body Height:**

Between 4.484 inches and 4.516 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 0.953 inches and 0.985 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.953 inches and 0.985 inches

**Reference Frequency Per Function:**

1.35 kilohertz blank

**Input Impedance Per Function W/load:**

50.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

10.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 blank

**Functional Terminal Type And Quantity:**

1 solder stud input 1st function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

1.00 kilohertz blank and 3.10 kilohertz blank and 3.14 kilohertz blank and 6.28 kilohertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 kilohertz blank and 3.10 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 3.0 blank and 40.00 blank and 40.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0