## NSN 5915-00-644-5706

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-644-5706

Overall	Length:
Overail	Lengui.

3.562 inches

**Overall Height:** 

2.313 inches

## **Overall Width:**

1.938 inches

## **Body Length:**

3.250 inches

#### **Body Width:**

1.938 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.432 inches and 1.442 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.745 inches and 2.755 inches

## **Operating Tempurature Range:**

## -40.0/+140.0 degrees celsius

## **Reference Frequency Per Function:**

1.0 kilohertz blank

## Input Impedance Per Function W/load:

10.0 kilohms blank

## **Output Impedance Per Function W/source Across Input:**

10.0 kilohms blank

## Mounting Facility Screw Thread Series Designator:

Unc

#### Inclosure Type:

Hermetically sealed

## Mounting Facility Type And Quantity:

4 threaded stud

## Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

## **Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

## **Specified Frequencies Of Discrimination Per Function:**

300.00 hertz blank and 3.00 kilohertz blank and 3.10 kilohertz blank and 4.00 kilohertz blank

## Thread Size:

0.138 inches

## Frequency Band Width Per Function:

300.00 hertz blank and 3.00 kilohertz blank

## Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 40.0 blank and 40.0 blank

## Style Designator:

Rectangular terminal/terminals on adjacent surfaces

# NSN 5915-00-644-5706

Low Pass Filter - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A047b0

