NSN 5915-00-644-5709

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-644-5709

Overall Height:

4.500 inches

Body Length:

2.750 inches

Body Width:

2.686 inches

Body Height:

4.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.125 inches

Operating Tempurature Range:

-0.0/+65.0 degrees celsius

Reference Frequency Per Function:

1.6 kilohertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

2 turret input 1st function

Specified Frequencies Of Discrimination Per Function:

100.00 hertz blank and 3.50 kilohertz blank and 5.00 kilohertz blank and 10.00 kilohertz blank

Thread Size:

0.190 inches

Frequency Band Width Per Function:

100.00 hertz blank and 3.50 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

 $50.0\,$ blank and $2.0\,$ blank and $2.0\,$ blank and $50.0\,$ blank

NSN 5915-00-644-5709

Low Pass Filter - Page 2 of 2



Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0