

View Online at https://aerobasegroup.com/nsn/5915-00-655-0083

| Overall Length:  |
|--|
| 5.062 inches   |
| Overall Height:  |
| 3.312 inches   |
| Body Length:   |
| 3.500 inches   |
| Body Width:  |
| 3.500 inches   |
| Body Height:   |
| 2.500 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.205 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 4.500 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:  |
| 2.000 inches   |
| Average Life Rating In Hours:  |
| 250.0  |
| Source Impedance Rating Per Function:  |
| 50.0 ohms blank  |
| Load Impedance Per Function:   |
| 50.0 ohms blank  |
| Power Line Frequency Rating Per Function In Hertz:                           |
| 60.0 blank   |
| Operating Current Rating Per Function In Amps:                               |
| 35.0 blank   |
| Maximum Voltage Drop Per Function:   |
| 500.0 millivolts dc blank  |
| Principal Circuitry Type Per Function:                                       |
| Inductance-capacitance blank   |
| Inclosure Type:  |
| Hermetically sealed  |
| Mounting Facility Type And Quantity:   |
| 4 unthreaded hole  |
| Functional Terminal Type And Quantity:                                       |
| 1 threaded stud output 2nd function  |
| Operating Voltage Rating And Type Per Function:                              |
| 125.0 volts ac blank and 400.0 volts dc blank                                |
| Body Material:   |
| Metal  |
| Body Surface Treatment:  |
| Tin  |



Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A047b0