NSN 5915-00-655-0347

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-655-0347

| Overall Height: |
|------------------------------------------------------------------------------|
| 5.841 inches |
| Body Length: |
| 2.100 inches |
| Body Width: |
| 1.600 inches |
| Body Height: |
| 4.100 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| Between 1.484 inches and 1.515 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+2000.0 |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 0.985 inches and 1.015 inches |
| Operating Tempurature Range: |
| -54.0/+70.0 degrees celsius |
| Average Life Rating In Hours: |
| 30000.0 |
| Source Impedance Rating Per Function: |
| 50.0 ohms 2nd radio interference |
| Load Impedance Per Function: |
| 50.0 ohms 2nd radio interference |
| Power Line Frequency Rating Per Function In Hertz: |
| 400.0 2nd radio interference |
| Operating Current Rating Per Function In Amps: |
| 5.0 2nd radio interference |
| Maximum Voltage Drop Per Function: |
| 1.2 volts ac 1st radio interference |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance 2nd radio interference |
| Input Terminal Manufacturer Code: |
| 02660 |
| Input Terminal Identification: |
| 348-25h10-03pn |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 4 threaded hole |

2 threaded stud output 2nd function

Functional Terminal Type And Quantity:

NSN 5915-00-655-0347

Radio Frequency Interference Filter - Page 2 of 2



Operating Voltage Rating And Type Per Function:

120.0 volts ac 2nd radio interference 2nd function

Thread Size:

0.164 inches

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0