NSN 5915-00-660-9262

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-660-9262

Overall Length:
5.703 inches
Overall Height:
1.000 inches
Body Length:
4.016 inches
Body Width:
1.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
3.562 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.906 inches
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Reference Frequency Per Function:
313.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
1.4 blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.35 blank
Functional Terminal Type And Quantity:
1 connector, receptacle output 2nd function
Specified Frequencies Of Discrimination Per Function:
225.00 megahertz blank and 400.00 megahertz blank and 550.00 megahertz blank and 950.00 megahertz blank
Thread Size:
0.138 inches
Body Material:
Metal
Frequency Band Width Per Function:

3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

NSN 5915-00-660-9262

Low Pass Filter - Page 2 of 2



Voltage Standing Wave Ratio Frequency Limits Per Function:

225.0 megahertz blank and 400.0 megahertz blank

Unpackaged Unit Weight:

9.000 ounces

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0