

View Online at <https://aerobasegroup.com/nsn/5915-00-672-2648>

Overall Height:

Between 2.281 inches and 2.593 inches

Body Length:

Between 2.125 inches and 2.250 inches

Body Width:

Between 1.625 inches and 1.750 inches

Body Height:

Between 2.062 inches and 2.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.625 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

Operating Temperature Range:

-55.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

2.55 kilohertz blank

Input Impedance Per Function W/load:

8.0 kilohms blank

Output Impedance Per Function W/source Across Input:

8.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Uninclosed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

80.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

2.25 kilohertz blank and 2.50 kilohertz blank and 2.60 kilohertz blank and 2.90 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

1.95 kilohertz blank and 3.30 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 6.0 blank and 6.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0