

View Online at <https://aerobasegroup.com/nsn/5915-00-672-2648>

**Overall Height:**

Between 2.281 inches and 2.593 inches

**Body Length:**

Between 2.125 inches and 2.250 inches

**Body Width:**

Between 1.625 inches and 1.750 inches

**Body Height:**

Between 2.062 inches and 2.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.625 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.000 inches

**Operating Temperature Range:**

-55.0/+65.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

2.55 kilohertz blank

**Input Impedance Per Function W/load:**

8.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

8.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Uninclosed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

80.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

2.25 kilohertz blank and 2.50 kilohertz blank and 2.60 kilohertz blank and 2.90 kilohertz blank

**Thread Size:**

0.138 inches

**Frequency Band Width Per Function:**

1.95 kilohertz blank and 3.30 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 6.0 blank and 6.0 blank and 40.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0