NSN 5915-00-675-0090

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-675-0090 **Overall Height:** 4.130 inches **Body Length:** 1.770 inches **Body Width:** 1.770 inches **Body Height:** 3.640 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.000 inches Vibration Resistance Range In Hertz: +5.0/+500.0 **Operating Tempurature Range:** -35.0/+75.0 degrees celsius **Reference Frequency Per Function:** 192.0 kilohertz blank Input Impedance Per Function W/load: 5.0 kilohms blank **Output Impedance Per Function W/source Across Input:** 100.0 kilohms blank **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type:** Hermetically sealed **Mounting Facility Type And Quantity:** 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 4.0 blank **Functional Terminal Type And Quantity:** 2 tab, solder lug output 2nd function **Specified Frequencies Of Discrimination Per Function:** 182.00 kilohertz blank and 190.00 kilohertz blank and 194.00 kilohertz blank and 202.00 kilohertz blank **Thread Size:** 0.164 inches **Body Material:** Metal

Frequency Band Width Per Function:

190.00 kilohertz blank and 194.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

32.0 blank and 5.0 blank and 5.0 blank and 52.0 blank

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

NSN 5915-00-675-0090

Band Pass Filter - Page 2 of 2



Sty	le	Des	ign	ato	r:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0