## NSN 5915-00-675-0091

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-675-0091

| Overall Height:   |
|---|
| 4.143 inches  |
| Body Length:  |
| 2.421 inches  |
| Body Width:   |
| 0.545 inches  |
| Body Height:  |
| 3.718 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:                            |
| 0.500 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:                             |
| 0.625 inches  |
| Operating Tempurature Range:  |
| -30.0/+65.0 degrees celsius   |
| Reference Frequency Per Function:   |
| 192.0 kilohertz blank   |
| Input Impedance Per Function W/load:  |
| 30.0 kilohms blank  |
| Output Impedance Per Function W/source Across Input:  |
| 240.0 kilohms blank   |
| Principal Circuitry Type Per Function:  |
| Inductance-resistance blank 2nd function  |
| Mounting Facility Screw Thread Series Designator:   |
| Unf   |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Type And Quantity:  |
| 2 threaded stud   |
| Insertion Loss At Reference Frequency Per Function In Decibels:   |
| 6.0 blank   |
| Functional Terminal Type And Quantity:  |
| 2 tab, solder lug ground 3rd function   |
| Specified Frequencies Of Discrimination Per Function:   |
| 191.00 kilohertz blank and 191.84 kilohertz blank and 192.16 kilohertz blank and 193.00 kilohertz blank |
| Thread Size:  |
| 0.190 inches  |
| Body Material:  |
| Metal   |
| Frequency Band Width Per Function:  |
| 191.84 kilohertz blank and 192.16 kilohertz blank   |
| Discrimination At Specificationified Frequencies Per Function In Decibels:                              |

50.0 blank and 3.0 blank and 50.0 blank

## NSN 5915-00-675-0091

Band Pass Filter - Page 2 of 2



| Style Designator:   |
|---------------------|
| Rectangular termina |

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0