## NSN 5915-00-679-0161

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-679-0161

View Online at https://aerobasegroup.com/nsn/5915-00-679-0161
Overall Height:
4.938 inches
Body Length:
1.594 inches
Body Width:
1.469 inches
Body Height:
4.469 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body
1.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body
1.000 inches
Reference Frequency Per Function:
82.0 hertz blank
Input Impedance Per Function W/load:
35.4 kilohms blank
Output Impedance Per Function W/source Across Input:
35.4 kilohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Mounting Facility Screw Thread Series Designator: Unc
Unc
Unc Inclosure Type:
Unc Inclosure Type: Hermetically sealed
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Thread Size:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Thread Size: 0.138 inches
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Thread Size: 0.138 inches Frequency Band Width Per Function:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Thread Size: 0.138 inches Frequency Band Width Per Function: 341.00 hertz blank and 1.23 kilohertz blank
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Thread Size: 0.138 inches Frequency Band Width Per Function: 341.00 hertz blank and 1.23 kilohertz blank Style Designator:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Thread Size: 0.138 inches Frequency Band Width Per Function: 341.00 hertz blank and 1.23 kilohertz blank Style Designator: Rectangular terminal/terminals on one surface
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Thread Size: 0.138 inches Frequency Band Width Per Function: 341.00 hertz blank and 1.23 kilohertz blank Style Designator: Rectangular terminal/terminals on one surface Shelf Life:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Thread Size: 0.138 inches Frequency Band Width Per Function: 341.00 hertz blank and 1.23 kilohertz blank Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a

Length:

Width:

No

## NSN 5915-00-679-0161

Band Pass Filter - Page 2 of 2

**Fiig:** A047b0

