

View Online at <https://aerobasegroup.com/nsn/5915-00-679-1971>

**Overall Height:**

2.188 inches

**Body Length:**

1.266 inches

**Body Width:**

1.266 inches

**Body Height:**

1.688 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.844 inches

**Vibration Resistance Range In Hertz:**

+10.0 to 55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.844 inches

**Operating Temperature Range:**

-55.0 to 85.0 degrees celsius

**Average Life Rating In Hours:**

2000.0

**Reference Frequency Per Function:**

400.0 hertz blank

**Input Impedance Per Function W/load:**

60.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

500.0 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance-resistance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

34.0 blank

**Functional Terminal Type And Quantity:**

1 turret output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

0.00 hertz blank and 200.00 hertz blank and 800.00 hertz blank and 801.00 hertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

200.00 hertz blank and 800.00 hertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

12.0 blank and 12.0 blank and 12.0 blank and 12.0 blank

**Maximum Dielectric Withstanding Dc Voltage:**

200.0 volts at sea level

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0