

View Online at <https://aerobasegroup.com/nsn/5915-00-679-1971>

Overall Height:

2.188 inches

Body Length:

1.266 inches

Body Width:

1.266 inches

Body Height:

1.688 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.844 inches

Vibration Resistance Range In Hertz:

+10.0 to 55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.844 inches

Operating Temperature Range:

-55.0 to 85.0 degrees celsius

Average Life Rating In Hours:

2000.0

Reference Frequency Per Function:

400.0 hertz blank

Input Impedance Per Function W/load:

60.0 kilohms blank

Output Impedance Per Function W/source Across Input:

500.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

34.0 blank

Functional Terminal Type And Quantity:

1 turret output 2nd function

Specified Frequencies Of Discrimination Per Function:

0.00 hertz blank and 200.00 hertz blank and 800.00 hertz blank and 801.00 hertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

200.00 hertz blank and 800.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

12.0 blank and 12.0 blank and 12.0 blank and 12.0 blank

Maximum Dielectric Withstanding Dc Voltage:

200.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0