

View Online at <https://aerobasegroup.com/nsn/5915-00-682-2964>

Overall Height:

3.000 inches

Body Length:

3.500 inches

Body Width:

1.438 inches

Body Height:

2.625 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.000 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

2.905 kilohertz blank

Source Impedance Rating Per Function:

500.0 ohms blank

Load Impedance Per Function:

500.0 ohms blank

Input Impedance Per Function W/load:

500.0 ohms blank

Output Impedance Per Function W/source Across Input:

500.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

5.0 blank

Functional Terminal Type And Quantity:

2 turret input 1st function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

2.78 kilohertz blank and 2.8625 kilohertz blank and 2.9475 kilohertz blank and 3.03 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

2.8625 kilohertz blank and 2.9475 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

16.0 blank and 0.7 blank and 0.7 blank and 16.0 blank

Special Features:

Terminals on surface opposite mtg surface

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0