NSN 5915-00-690-9392

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-690-9392

Body Length:
6.000 inches
Body Width:
1.438 inches
Body Height:
3.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
5.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.875 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Reference Frequency Per Function:
1.105 kilohertz blank
Source Impedance Rating Per Function:
600.0 ohms blank
Load Impedance Per Function:
90.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Inclosure Type:
Inclosure Type: Hermetically sealed
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 11.0 blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 11.0 blank Functional Terminal Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 11.0 blank Functional Terminal Type And Quantity: 2 threaded stud input 1st function
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 11.0 blank Functional Terminal Type And Quantity: 2 threaded stud input 1st function Specified Frequencies Of Discrimination Per Function:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 11.0 blank Functional Terminal Type And Quantity: 2 threaded stud input 1st function Specified Frequencies Of Discrimination Per Function: 980.00 hertz blank and 1.02 kilohertz blank and 1.19 kilohertz blank and 1.23 kilohertz blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 11.0 blank Functional Terminal Type And Quantity: 2 threaded stud input 1st function Specified Frequencies Of Discrimination Per Function: 980.00 hertz blank and 1.02 kilohertz blank and 1.19 kilohertz blank and 1.23 kilohertz blank Thread Size:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 11.0 blank Functional Terminal Type And Quantity: 2 threaded stud input 1st function Specified Frequencies Of Discrimination Per Function: 980.00 hertz blank and 1.02 kilohertz blank and 1.19 kilohertz blank and 1.23 kilohertz blank Thread Size: 0.138 inches
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 11.0 blank Functional Terminal Type And Quantity: 2 threaded stud input 1st function Specified Frequencies Of Discrimination Per Function: 980.00 hertz blank and 1.02 kilohertz blank and 1.19 kilohertz blank and 1.23 kilohertz blank Thread Size: 0.138 inches Body Material:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 11.0 blank Functional Terminal Type And Quantity: 2 threaded stud input 1st function Specified Frequencies Of Discrimination Per Function: 980.00 hertz blank and 1.02 kilohertz blank and 1.19 kilohertz blank and 1.23 kilohertz blank Thread Size: 0.138 inches Body Material: Metal
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 11.0 blank Functional Terminal Type And Quantity: 2 threaded stud input 1st function Specified Frequencies Of Discrimination Per Function: 980.00 hertz blank and 1.02 kilohertz blank and 1.19 kilohertz blank and 1.23 kilohertz blank Thread Size: 0.138 inches Body Material: Metal Frequency Band Width Per Function:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 11.0 blank Functional Terminal Type And Quantity: 2 threaded stud input 1st function Specified Frequencies Of Discrimination Per Function: 980.00 hertz blank and 1.02 kilohertz blank and 1.19 kilohertz blank and 1.23 kilohertz blank Thread Size: 0.138 inches Body Material: Metal Frequency Band Width Per Function: 1.02 kilohertz blank and 1.19 kilohertz blank

N/a

Shelf Life:

Rectangular terminal/terminals on one surface

NSN 5915-00-690-9392

Band Pass Filter - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A047b0