

View Online at <https://aerobasegroup.com/nsn/5915-00-690-9405>

Overall Height:

3.375 inches

Body Length:

6.000 inches

Body Width:

1.440 inches

Body Height:

3.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.250 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.875 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

2.125 kilohertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Load Impedance Per Function:

75.0 kilohms blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

75.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

11.0 blank

Functional Terminal Type And Quantity:

2 turret input 1st function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

2.00 kilohertz blank and 2.1225 kilohertz blank and 2.1685 kilohertz blank and 2.25 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

2.1225 kilohertz blank and 2.1685 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

45.0 blank and 2.5 blank and 2.5 blank and 45.0 blank

Unpackaged Unit Weight:

1.938 pounds

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0