

View Online at <https://aerobasegroup.com/nsn/5915-00-690-9411>

**Body Length:**

6.000 inches

**Body Width:**

1.440 inches

**Body Height:**

3.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

5.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.875 inches

**Operating Temperature Range:**

-0.0/+65.0 degrees celsius

**Reference Frequency Per Function:**

2.635 kilohertz blank

**Source Impedance Rating Per Function:**

600.0 ohms blank

**Load Impedance Per Function:**

600.0 ohms blank

**Input Impedance Per Function W/load:**

600.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

75.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

1 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

11.0 blank

**Functional Terminal Type And Quantity:**

3 tab, solder lug ground 3rd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

2.51 kilohertz blank and 2.5925 kilohertz blank and 2.6775 kilohertz blank and 2.76 kilohertz blank

**Thread Size:**

0.138 inches

**Frequency Band Width Per Function:**

2.5925 kilohertz blank and 2.6775 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

45.0 blank and 2.5 blank and 2.5 blank and 45.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Test Data Document:**

96238-43000005 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0