

View Online at <https://aerobasegroup.com/nsn/5915-00-690-9413>

Body Length:

6.000 inches

Body Width:

1.440 inches

Body Height:

3.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.875 inches

Operating Temperature Range:

-0.0/+65.0 degrees celsius

Reference Frequency Per Function:

2.34 kilohertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

75.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

11.0 blank

Functional Terminal Type And Quantity:

3 tab, solder lug ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

2.34 kilohertz blank and 2.4225 kilohertz blank and 2.5075 kilohertz blank and 2.59 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

2.4225 kilohertz blank and 2.5075 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

45.0 blank and 2.5 blank and 2.5 blank and 45.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0