## NSN 5915-00-710-9513

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-710-9513

| Overall Height:  |  |  |  |  |
|--|--|--|--|--|
| 4.109 inches   |  |  |  |  |
| Body Length:   |  |  |  |  |
| 2.750 inches   |  |  |  |  |
| Body Width:  |  |  |  |  |
| 2.375 inches   |  |  |  |  |
| Body Height:   |  |  |  |  |
| 3.812 inches   |  |  |  |  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:           |  |  |  |  |
| 2.875 inches   |  |  |  |  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:            |  |  |  |  |
| 1.750 inches   |  |  |  |  |
| Operating Tempurature Range:   |  |  |  |  |
| +0.0/+55.0 degrees celsius   |  |  |  |  |
| Reference Frequency Per Function:  |  |  |  |  |
| 400.0 hertz blank  |  |  |  |  |
| Input Impedance Per Function W/load:   |  |  |  |  |
| 620.0 ohms blank   |  |  |  |  |
| Output Impedance Per Function W/source Across Input:                                   |  |  |  |  |
| 2.0 kilohms blank  |  |  |  |  |
| Principal Circuitry Type Per Function:   |  |  |  |  |
| Inductance-capacitance blank   |  |  |  |  |
| Mounting Facility Screw Thread Series Designator:                                      |  |  |  |  |
| Unc  |  |  |  |  |
| Inclosure Type:  |  |  |  |  |
| Hermetically sealed  |  |  |  |  |
| Mounting Facility Type And Quantity:   |  |  |  |  |
| 4 threaded stud  |  |  |  |  |
| Insertion Loss At Reference Frequency Per Function In Decibels:                        |  |  |  |  |
| 6.0 blank  |  |  |  |  |
| Functional Terminal Type And Quantity:   |  |  |  |  |
| 1 tab, solder lug output 2nd function  |  |  |  |  |
| Specified Frequencies Of Discrimination Per Function:                                  |  |  |  |  |
| 58.60 hertz blank and 758.60 hertz blank and 800.00 hertz blank and 835.00 hertz blank |  |  |  |  |
| Thread Size:   |  |  |  |  |
| 0.138 inches   |  |  |  |  |
| Body Material:   |  |  |  |  |
| Metal  |  |  |  |  |
| Frequency Band Width Per Function:   |  |  |  |  |
| 58.60 hertz blank and 758.60 hertz blank   |  |  |  |  |
| Discrimination At Specificationified Frequencies Per Function In Decibels:             |  |  |  |  |

3.0 blank and 3.0 blank and 20.0 blank and 20.0 blank

## NSN 5915-00-710-9513

Low Pass Filter - Page 2 of 2



| Style | Des | igna | tor: |
|-------|-----|------|------|
|       |     |      |      |

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0