NSN 5915-00-711-4630

Low Pass Filter - Page 1 of 2

Overall Height: 2.000 inches Body Length: 1.312 inches Body Width:



View Online at https://aerobasegroup.com/nsn/5915-00-711-4630

1.312 inches
Body Height:
1.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.884 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.884 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
3.0 kilohertz blank
Input Impedance Per Function W/load:
1.0 kilohms blank
Output Impedance Per Function W/source Across Input:
1.0 kilohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
6.0 blank
Functional Terminal Type And Quantity:
1 wire hook output 2nd function
Specified Frequencies Of Discrimination Per Function:
0.00 hertz blank and 6.00 kilohertz blank and 6.50 kilohertz blank and 50.00 kilohertz blank
Thread Size:
0.138 inches
Frequency Band Width Per Function:
0.00 hertz blank and 6.00 kilohertz blank

NSN 5915-00-711-4630

Low Pass Filter - Page 2 of 2



Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 6.0 blank and 15.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0