

View Online at <https://aerobasegroup.com/nsn/5915-00-718-5452>

Overall Height:

2.875 inches

Body Length:

1.688 inches

Body Width:

1.188 inches

Body Height:

2.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Operating Temperature Range:

-55.0/+70.0 degrees celsius

Reference Frequency Per Function:

40.0 hertz blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 100.00 hertz blank and 150.00 hertz blank and 200.00 hertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 100.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 6.0 blank and 35.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

81349-milf18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0