

View Online at <https://aerobasegroup.com/nsn/5915-00-718-5452>

**Overall Height:**

2.875 inches

**Body Length:**

1.688 inches

**Body Width:**

1.188 inches

**Body Height:**

2.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Operating Temperature Range:**

-55.0/+70.0 degrees celsius

**Reference Frequency Per Function:**

40.0 hertz blank

**Input Impedance Per Function W/load:**

10.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

10.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 100.00 hertz blank and 150.00 hertz blank and 200.00 hertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 100.00 hertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 6.0 blank and 35.0 blank and 40.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Test Data Document:**

81349-milf18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0