

View Online at <https://aerobasegroup.com/nsn/5915-00-722-7928>

Overall Length:

5.594 inches

Body Outside Diameter:

0.750 inches

Vibration Resistance Range In Hertz:

+5.0/+500.0

Operating Temperature Range:

-54.0/+71.0 degrees celsius

Average Life Rating In Hours:

250.0

Reference Frequency Per Function:

1.10 composition b grade a two phase to two phase

Input Impedance Per Function W/load:

50.0 ohms 2nd band pass

Output Impedance Per Function W/source Across Input:

50.0 ohms 1st band pass

Voltage Standing Wave Ratio Per Function:

1.5 2nd band pass

Average Power Rating Per Function:

15.0 watts 2nd band pass 2nd function

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 2nd band pass

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

340.00 megahertz 2nd band pass 2nd function and 1.09 gigahertz 2nd band pass 2nd function and 1.11 gigahertz 2nd band pass 2nd function and 2.00 gigahertz 2nd band pass 2nd function

Frequency Band Width Per Function:

1.09 gigahertz 2nd band pass and 1.11 gigahertz 2nd band pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 2nd band pass 2nd function and 3.0 2nd band pass 2nd function and 3.0 2nd band pass 2nd function and 40.0 2nd band pass 2nd function

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.09 composition b grade a two phase to two phase and 1.11 composition b grade a two phase to two phase

Unpackaged Unit Weight:

8.000 ounces

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0