

View Online at <https://aerobasegroup.com/nsn/5915-00-725-8399>

**Overall Height:**

2.032 inches

**Body Length:**

7.375 inches

**Body Width:**

2.750 inches

**Body Height:**

1.875 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

6.900 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.800 inches

**Operating Temperature Range:**

-10.0/+65.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

96.0 kilohertz blank

**Input Impedance Per Function W/load:**

5.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

200.0 ohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

5.0 blank

**Functional Terminal Type And Quantity:**

2 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

88.00 kilohertz blank and 94.56 kilohertz blank and 97.44 kilohertz blank and 104.00 kilohertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

94.56 kilohertz blank and 97.44 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

65.0 blank and 1.0 blank and 1.0 blank and 65.0 blank

**Maximum Dielectric Withstanding Dc Voltage:**

100.0 volts at sea level

**Special Features:**

1 capacitor terminal to be used in component approval tests

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0