NSN 5915-00-726-4383

High Pass Filter - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5915-00-726-4383

view online at https://defobasegroup.com/non/conto to 120 4000
Body Length:
2.250 inches
Body Width:
2.000 inches
Body Height:
3.060 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.690 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.440 inches
Reference Frequency Per Function:
50.15 kilohertz blank
Source Impedance Rating Per Function:
5.0 kilohms blank
Load Impedance Per Function:
5.0 kilohms blank
Input Impedance Per Function W/load:
5.0 kilohms blank
Output Impedance Per Function W/source Across Input:
5.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Unc Inclosure Type:
Inclosure Type:
Inclosure Type: Encased
Inclosure Type: Encased Mounting Facility Type And Quantity:
Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded stud
Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:
Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank
Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity:
Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 turret output 2nd function
Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 turret output 2nd function Specified Frequencies Of Discrimination Per Function:
Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 turret output 2nd function Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 100.00 hertz blank and 300.00 hertz blank and 100.00 kilohertz blank
Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 turret output 2nd function Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 100.00 hertz blank and 300.00 hertz blank and 100.00 kilohertz blank
Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 turret output 2nd function Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 100.00 hertz blank and 300.00 hertz blank and 100.00 kilohertz blank Thread Size: 0.138 inches
Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 turret output 2nd function Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 100.00 hertz blank and 300.00 hertz blank and 100.00 kilohertz blank Thread Size: 0.138 inches Frequency Band Width Per Function:
Inclosure Type:EncasedMounting Facility Type And Quantity:4 threaded studInsertion Loss At Reference Frequency Per Function In Decibels:1.0 blankFunctional Terminal Type And Quantity:1 turret output 2nd functionSpecified Frequencies Of Discrimination Per Function:0.00 hertz blank and 100.00 hertz blank and 300.00 hertz blank and 100.00 kilohertz blankThread Size:0.138 inchesFrequency Band Width Per Function:300.00 hertz blank and 100.00 kilohertz blank
Inclosure Type:EncasedMounting Facility Type And Quantity:4 threaded studInsertion Loss At Reference Frequency Per Function In Decibels:1.0 blankFunctional Terminal Type And Quantity:1 turret output 2nd functionSpecified Frequencies Of Discrimination Per Function:0.00 hertz blank and 100.00 hertz blank and 300.00 hertz blank and 100.00 kilohertz blankThread Size:0.138 inchesFrequency Band Width Per Function:300.00 hertz blank and 100.00 kilohertz blankDiscrimination At Specificationified Frequencies Per Function In Decibels:
Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 turret output 2nd function Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 100.00 hertz blank and 300.00 hertz blank and 100.00 kilohertz blank Thread Size: 0.138 inches Frequency Band Width Per Function: 300.00 hertz blank and 100.00 kilohertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 50.0 blank and 50.0 blank and 1.5 blank and 1.5 blank

NSN 5915-00-726-4383

High Pass Filter - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0

