## NSN 5915-00-726-4387

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-726-4387

Overall Height:
3.440 inches
Body Length:
2.250 inches
Body Width:
2.000 inches
Body Height:
3.060 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.690 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.440 inches
Reference Frequency Per Function:
1.75 kilohertz blank
Input Impedance Per Function W/load:
10.0 kilohms blank
Output Impedance Per Function W/source Across Input:
10.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
1.0 blank
Functional Terminal Type And Quantity:
1 solder stud input 1st function
Specified Frequencies Of Discrimination Per Function:
0.00 hertz blank and 3.50 kilohertz blank and 5.00 kilohertz blank and 10.00 kilohertz blank
Thread Size:
0.138 inches
Body Material:
Metal
Frequency Band Width Per Function:
0.00 hertz blank and 3.50 kilohertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
1.0 blank and 1.0 blank and 50.0 blank and 50.0 blank
Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on one surface

## NSN 5915-00-726-4387

Low Pass Filter - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0